



Policy for Private Piping Under Municipal Roads

Overview:

Whereas farmers may be making requests to bury culvert or solid wall pipes under/through municipal roads, this policy has been developed to set the standards for these installations.

Policy:

1. The land adjacent to the road where the installation will take place must be either owned by the applicant, or written permission must be obtained from the owners.
2. All installations to be done under the supervision of the Public Works Supervisor or his/her designate.
3. The applicant will either swab the piping/culvert or cap it, at the completion of the pumping.
4. The applicant will enter into an agreement with the municipality stipulating the conditions of
 - i. installation and maintenance for the installation at Council's discretion.

Culverts:

1. The culvert will be installed above the drainage level of the ditch.
2. The applicant will be responsible for the graveling and maintenance of the crossing on an ongoing basis as long as this procedure is in place.

Solid Wall Pipe:

1. The piping to be installed as follows:
 - where there are no municipal waterlines: 1.2 meters below the bottom of the ditch; and
 - where there is a municipal waterline: 0.5 meters below the waterline.

2. The applicant will be responsible for the graveling and maintenance of the crossing on an ongoing basis as long as this procedure is in place.

Reviewed and Accepted February 27, 2024, Resolution No. 42/24
Accepted as Policy on April 27, 2016, by Resolution No. 138/16